## NSN 5305-01-332-8609

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-332-8609

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.231 inches and 0.312 inches
Fastener Length:
Between 0.281 inches and 0.312 inches
Head Style:
Fillister
Head Diameter:
Between 0.178 inches and 0.183 inches
Head Height:
Between 0.059 inches and 0.069 inches
Hole Diameter:
Between 0.034 inches and 0.042 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.112 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Bearing Surface Of Head Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc

## NSN 5305-01-332-8609

Machine Screw - Page 2 of 2



	ation Data:	Ca	ifi	С	е	3p	٤
--	-------------	----	-----	---	---	----	---

80205-nas1101 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0