

View Online at <https://aerobasegroup.com/nsn/5305-01-332-8611>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.284 inches and 0.437 inches

Fastener Length:

Between 0.406 inches and 0.437 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.238 inches and 0.279 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Copper alloy 268 or copper alloy 260 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 274 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 240 or copper alloy 342

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 3 style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0