NSN 5305-01-333-6080

Machine Screw - Page 1 of 2

Thread Class:





3a **Thread Direction: Right-hand Thread Length:** 0.578 inches Fastener Length: Between 0.672 inches and 0.719 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.093 inches Width Between Flats: Between 0.243 inches and 0.251 inches Internal Drive Style: Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 63.0 microinches Shank Surface Finish: 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1802 professional/industrial association standard Shelf Life: N/a

NSN 5305-01-333-6080

Machine Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

