

View Online at <https://aerobasegroup.com/nsn/5305-01-333-6386>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

Between 0.449 inches and 0.479 inches

Head Style:

Fillister

Head Diameter:

Between 0.360 inches and 0.370 inches

Head Height:

Between 0.095 inches and 0.100 inches

Locking Feature:

Strip threads

First Diameter From Head:

Between 0.115 inches and 0.118 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.172 inches and 0.202 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Features Provided:

O ring and shim

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Special Features:

Shim made of polytetrafluoroethylene

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 fastener

Material Specification:

L-p-385 assn standard single material response locking feature

Surface Treatment:

Oxide fastener

Surface Treatment Specification:

Mil-c-13924 cl 2 military specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.