NSN 5305-01-333-9865

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-333-9865 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.270 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **First Diameter From Head:** Between 0.184 inches and 0.188 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.450 inches and 0.520 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 24.0 rockwell c and 36.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5736 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Unf

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-01-333-9865

Externally Relieved Body Screw - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0