NSN 5305-01-333-9881

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-333-9881 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 3.800 inches and 4.000 inches **Fastener Length:** 4.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.740 inches and 0.750 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: 0.625 inches Thready Qty Per Inch (tpi): 10 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 37.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 153000 pounds per square inch Material: Steel **Surface Treatment:** Aluminum and chromate or zinc and chromate **Surface Treatment Specification:** Mil-c-83488, type 2 cl 3 military specification 1st treatment response or mil-c-87115, cl 3 military specification 2nd treatment response **Thread Series Designator:** Unrc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-333-9881

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.