

View Online at <https://aerobasegroup.com/nsn/5305-01-334-0523>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.500 inches

**Fastener Length:**

1.860 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.378 inches and 0.403 inches

**Width Between Flats:**

Between 0.922 inches and 0.938 inches

**Shank Unthreaded Hole Diameter:**

0.125 inches first hole and 0.129 inches first hole

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

11

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.641 inches first hole

**Color:**

Black

**Material:**

Steel

**Material Specification:**

Sae j429 gr5 assn standard single material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633 ty2 sc2 assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0