

View Online at <https://aerobasegroup.com/nsn/5305-01-334-1158>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.185 inches and 0.265 inches

**Fastener Length:**

Between 0.235 inches and 0.265 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Locking Feature:**

Patch

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Screw Material:**

Iron alloy 660

**Locking Feature Material:**

Plastic polyamide

**Screw Material Specification:**

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1216 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0