## NSN 5305-01-334-3622

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-334-3622

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.403 inches
Fastener Length:
Between 1.263 inches and 1.293 inches
Head Style:
Flat countersunk
Head Diameter:
0.3988 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.250 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416, type 2, class 2 federal specification single treatment response
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416, type 2, class 2 federal specification single treatment response  Thread Series Designator:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416, type 2, class 2 federal specification single treatment response  Thread Series Designator:  Unjf

N/a

## NSN 5305-01-334-3622

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0