NSN 5305-01-334-3902

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-334-3902

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.250 inches and 0.312 inches
Fastener Length:
0.312 inches
Head Style:
Pan
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.087 inches and 0.097 inches
Locking Feature:
Pellet or strip
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polyamide
Plastic polyamide Screw Material Specification:
1 ,
Screw Material Specification:
Screw Material Specification: Ams5737 assn standard single material response
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment:
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Passivate
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification:
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data:
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life:

--

NSN 5305-01-334-3902

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0