Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-334-4638

view Online at https://defoba	segioup.com/man/3000-01-004-4000
Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.275 inches and 0.	285 inches
Fastener Length:	
Between 0.344 inches and 0.	375 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.256 inches and 0.	270 inches
Head Height:	
Between 0.087 inches and 0.	097 inches
First Diameter From Head:	
Between 0.093 inches and 0.	097 inches
Distance From Largest Bea	ring Surface Of Head To End Of First Diameter:
Between 0.090 inches and 0.	100 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.138 inches	
Thready Qty Per Inch (tpi):	
32	
Externally Relieved Body D	iameter Quantity:
1	
Material:	
Steel comp 301 or steel com	p 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel com	p 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or steel com	p 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel
comp 385	
Surface Treatment:	
Passivate	
Surface Treatment Specific	ation:
Astm a380 assn standard sin	gle treatment response
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
4002b0	