## NSN 5305-01-334-4649

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-334-4649

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.298 inches and 0.348 inches
Fastener Length:
Between 0.620 inches and 0.650 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Locking Feature:
Patch threads
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Color:
Green threads
Material:
Plastic polyamide locking feature
Material Specification:
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response fastener
Thread Series Designator:
Unjf

## NSN 5305-01-334-4649

Close Tolerance Screw - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

80205-nas7803 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0