NSN 5305-01-334-6655

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-334-6655 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.110 inches and 0.140 inches **Fastener Length:** Between 0.797 inches and 0.827 inches **Head Style:** Knurled no. 2 **Head Diameter:** 0.265 inches **Head Height:** 0.097 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Tactical air opns module (an/tyq (23); 485l tacs **Material Accommodated Thickness:** Between 0.064 inches and 0.125 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 304 stand-off **Material Specification:** Mil-s-5059 military specification single material response secondary washer **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A003b0

NSN 5305-01-334-6655

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-23195 spec.