NSN 5305-01-334-6988

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-334-6988
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.137 inches
Fastener Length:
Between 0.150 inches and 0.160 inches
Head Style:
Pan
Head Diameter:
Between 0.145 inches and 0.155 inches
Head Height:
Between 0.027 inches and 0.032 inches
Shoulder Diameter:
0.086 inches first shoulder and 0.090 inches first shoulder
Shoulder Length:
0.018 inches first shoulder and 0.028 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.060 inches
Thready Qty Per Inch (tpi):
80
Shoulder Shape:
Round first shoulder
Material:
Steel comp 303
Material Specification:
Qq-s-764, cond a federal specification all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-36, ty iv assn standard single treatment response
Test Data Document:
81349-mil-c-28754 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf
Specification Data:
81349-mil-c-28754/40 government specification

N/a

Shelf Life:

NSN 5305-01-334-6988

Shoulder Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0