## NSN 5305-01-334-7350

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-334-7350 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.174 inches **Fastener Length:** 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.078 inches and 0.082 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.451 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point, optional Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

**Unit Of Measure:** 

3 type and 9 style

Shelf Life:

N/a

**Specification Or Standard:** 

## NSN 5305-01-334-7350

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0