

View Online at <https://aerobasegroup.com/nsn/5305-01-334-7350>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.174 inches

Fastener Length:

0.625 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

First Diameter From Head:

Between 0.078 inches and 0.082 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.451 inches

Internal Drive Style:

Cross recess type iii

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Externally Relieved Body Diameter Quantity:

1

Special Features:

Cone point, optional

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9 style

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0