NSN 5305-01-334-7363

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-334-7363

| Thread Class: |
|--|
| 3a |
| Sa Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.400 inches and 0.450 inches |
| |
| Fastener Length: Between 0.598 inches and 0.628 inches |
| |
| Head Style: Flat countersunk |
| Head Diameter: |
| Between 0.464 inches and 0.506 inches |
| Shoulder Diameter: |
| |
| 0.280 inches first shoulder and 0.281 inches first shoulder |
| Shoulder Length: |
| 0.178 inches first shoulder and 0.198 inches first shoulder |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Shoulder Shape: |
| Round first shoulder |
| Product Name: |
| Navy special project |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1790 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-334-7363

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

