## NSN 5305-01-334-8557

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-334-8557 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.400 inches and 0.450 inches **Fastener Length:** Between 0.722 inches and 0.752 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.506 inches **Shoulder Diameter:** 0.264 inches first shoulder and 0.265 inches first shoulder **Shoulder Length:** 0.302 inches first shoulder and 0.322 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1790 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-334-8557

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0