

View Online at <https://aerobasegroup.com/nsn/5305-01-334-8681>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.166 inches and 0.188 inches

**Fastener Length:**

Between 0.172 inches and 0.204 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.267 inches and 0.279 inches

**Locking Feature:**

Patch

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Navy special project

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams5731 assn standard single material response or ms5737 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1741 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0