## NSN 5305-01-335-7409

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-335-7409 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.281 inches and 0.375 inches **Fastener Length:** Between 0.343 inches and 0.375 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1524 or steel comp 1527 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1132 **Screw Surface Treatment:** Zinc and chromate **Screw Surface Treatment Specification:** Astm b633 fe/zn5 type 2 assn standard single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

A500d0

**Demilitarization:**