

View Online at <https://aerobasegroup.com/nsn/5305-01-335-7411>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.528 inches and 0.620 inches

Fastener Length:

Between 0.590 inches and 0.620 inches

Head Style:

Fillister extended washer

Head Diameter:

Between 0.353 inches and 0.373 inches

Head Height:

Between 0.085 inches and 0.105 inches

Extended Washer Diameter:

Between 0.413 inches and 0.443 inches

Extended Washer Thickness:

Between 0.030 inches and 0.037 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Steel comp 4340 or steel comp 8740

Screw Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas8303 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.