NSN 5305-01-336-0760

Machine Screw - Page 1 of 2

Thread Class:

3a



View Online at https://aerobasegroup.com/nsn/5305-01-336-0760

| Thread Direction: |
|--|
| Right-hand |
| Thread Length: |
| 0.542 inches |
| Fastener Length: |
| Between 0.613 inches and 0.644 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.442 inches and 0.507 inches |
| Locking Feature: |
| Strip |
| Internal Drive Style: |
| Torque set |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| Between 36.0 rockwell c and 40.0 rockwell c |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Screw Material: |
| Iron alloy 660 |
| Locking Feature Material: |
| Plastic polychlorotrifluoroethylene |
| Screw Material Specification: |
| Ams 5737 assn standard single material response |
| Locking Feature Material Specification: |
| Ams 3650 assn standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1189 professional/industrial association standard |

NSN 5305-01-336-0760

Machine Screw - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0