NSN 5305-01-336-0760

Machine Screw - Page 1 of 2

Thread Class:

3a



View Online at https://aerobasegroup.com/nsn/5305-01-336-0760

Thread Direction:
Right-hand
Thread Length:
0.542 inches
Fastener Length:
Between 0.613 inches and 0.644 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.442 inches and 0.507 inches
Locking Feature:
Strip
Internal Drive Style:
Torque set
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polychlorotrifluoroethylene
Screw Material Specification:
Ams 5737 assn standard single material response
Locking Feature Material Specification:
Ams 3650 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1189 professional/industrial association standard

NSN 5305-01-336-0760

Machine Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0