NSN 5305-01-336-3211

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-336-3211 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.589 inches and 0.625 inches **Fastener Length:** 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.154 inches and 0.161 inches **Head Height:** Between 0.095 inches and 0.099 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.099 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-336-3211

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0