NSN 5305-01-336-6321

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-336-6321

80205-nas7503 professional/industrial association standard

Thread Class:
3a
Thread Direction:
Right-hand Thread Length:
Thread Length:
0.323 inches
Fastener Length:
Between 0.433 inches and 0.463 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.338 inches and 0.381 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
160000 pounds per square inch Hardness Rating:
Hardness Rating:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response

NSN 5305-01-336-6321

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0