NSN 5305-01-336-7540

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-336-7540 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.325 inches **Fastener Length:** 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** Between 0.080 inches and 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.290 inches and 0.310 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Thread Series Designator:** Unrc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-336-7540

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0