NSN 5305-01-336-9603

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-336-9603 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.202 inches **Fastener Length:** Between 0.296 inches and 0.343 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 63.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc **Specification Data:**

Shelf Life: N/a

80205-nas1802 professional/industrial association standard

NSN 5305-01-336-9603

Machine Screw - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A500d0