

View Online at <https://aerobasegroup.com/nsn/5305-01-336-9808>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.380 inches

**Fastener Length:**

Between 0.830 inches and 0.888 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.306 inches and 0.322 inches

**Head Height:**

Between 0.085 inches and 0.096 inches

**First Diameter From Head:**

Between 0.115 inches and 0.125 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.474 inches and 0.484 inches

**Point Style:**

Cone

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Color:**

Black

**Material:**

Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 304 or steel comp 304l

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, cl4 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.