# NSN 5305-01-337-1144

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-337-1144



### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.100 inches and 0.193 inches

#### Fastener Length:

Between 0.219 inches and 0.250 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.231 inches and 0.279 inches

#### Locking Feature:

Patch

#### **Internal Drive Style:**

Torque set

## Thread Diameter:

0.138 inches

### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Screw Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

#### Locking Feature Material:

Plastic polyamide

#### Screw Surface Treatment:

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

#### **Thread Series Designator:**

Unjc

#### **Specification Data:**

80205-nas1189 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-01-337-1144

Machine Screw - Page 2 of 2

Fiig: A500d0

