NSN 5305-01-337-2692

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-337-2692



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.162 inches and 0.255 inches Fastener Length: Between 0.281 inches and 0.312 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.231 inches and 0.279 inches Locking Feature: Patch **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Locking Feature Material:

Plastic polyamide

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1189 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-337-2692

Machine Screw - Page 2 of 2

Fiig: A500d0

