NSN 5305-01-337-2693

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-2693 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.225 inches and 0.318 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.231 inches and 0.279 inches **Locking Feature:** Patch **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Locking Feature Material:** Plastic polyamide **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:**

Qq-p-416, ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1189 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-337-2693

Machine Screw - Page 2 of 2



Fiig:

A500d0