NSN 5305-01-337-2695

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-2695

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.407 inches and 0.500 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Locking Feature:
Patch
Internal Drive Style:
Torque set
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Locking Feature Material:
Plastic polyamide
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1190 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-337-2695

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0