

View Online at <https://aerobasegroup.com/nsn/5305-01-337-3297>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.656 inches

**Fastener Length:**

Between 1.953 inches and 1.983 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.810 inches and 0.889 inches

**Grip Diameter:**

Between 0.4365 inches and 0.4370 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.437 inches

**Grip Length:**

Between 1.302 inches and 1.322 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Special Features:**

Tapped hole in head 0.138-32 unjc-3b threads. Distance from top of head to injection port 0.930 nom. Inch. Injection port 0.120 nom. In. Lg; 0.060 nom. In. Wide

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0