

View Online at <https://aerobasegroup.com/nsn/5305-01-337-3299>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.906 inches

Fastener Length:

Between 2.266 inches and 2.296 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.047 inches and 1.144 inches

Grip Diameter:

Between 0.5610 inches and 0.5615 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.562 inches

Grip Length:

Between 1.365 inches and 1.385 inches

Thready Qty Per Inch (tpi):

18

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Special Features:

Tapped hole in head 0.138-32 unjc-3b threads, distance from top of head to injection port 0.930 nom. Inch. Injection port 0.120 nom. In. Lg; 0.060 nom. In. Wide

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0