NSN 5305-01-337-3303

Close Tolerance Screw - Page 1 of 2

Unjf



View Online at https://aerobasegroup.com/nsn/5305-01-337-3303

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.501 inches
Fastener Length:
Between 1.547 inches and 1.594 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.602 inches and 0.634 inches
Head Height:
Between 0.088 inches and 0.090 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Features Provided:
O ring
Thready Qty Per Inch (tpi):
24
Z-+ Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Rubber butadiene-acrylonitrile class nbr ringtitanium alloy uns r56400 fastener
Material Specification:
Ams 4967 assn standard single material response fastener
Surface Treatment:
Phosphate fastener Surface Treatment Specification:
Bac5861, cagec 81205 mfr ref single treatment response fastener
Thread Series Designator:

NSN 5305-01-337-3303

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

