## NSN 5305-01-337-3801

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-3801

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.469 inches	
Fastener Length:	
Between 1.142 inches and 1.172 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.456 inches and 0.508 inches	
Grip Diameter:	
Between 0.249 inches and 0.2495 inches	
Internal Drive Style:	
High-torque	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 0.678 inches and 0.698 inches	
Thready Qty Per Inch (tpi):	
28	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
Surface Finish:	
32.0 microinches bearing surface of head32.0 microinches grip32.0 micr	oinches threads
Product Name:	
Navy special project	
Special Features:	
Tapped hole in head 0.138-32 injc-3b threads. Distance from top of head	to injection port 0.420 nom. Inch. Injection port 0.120 nom. In. Lg;
0.060 nom. In. Wide	
Material:	
Titanium alloy uns r56400	
Material Specification:	
Ams 4928 assn standard single material response or ams 4967 assn sta	andard single material response
Surface Treatment:	
Phosphate	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5305-01-337-3801

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

