## NSN 5305-01-337-4859

Close Tolerance Screw - Page 1 of 2



0.120 nom. In. Lg;

View Online at https://aerobasegroup.com/nsn/5305-01-337-4859

	Class:
3a	
Thread	Direction:
Right-h	and
Thread	Length:
0.469 ir	nches
Fasten	er Length:
Betwee	n 1.266 inches and 1.296 inches
Head S	tyle:
Flat cou	Intersunk
Head D	iameter:
Betwee	n 0.456 inches and 0.508 inches
Grip Di	ameter:
Betwee	n 0.2490 inches and 0.2495 inches
Interna	I Drive Style:
High-to	rque
Thread	Diameter:
0.250 ir	nches
Grip Le	ength:
Betwee	n 0.802 inches and 0.822 inches
Thread	y Qty Per Inch (tpi):
28	
Counte	rsink Angle:
Betwee	n 99.0 degrees and 101.0 degrees
Surface	e Finish:
32.0 mi	croinches bearing surface of head32.0 microinches grip32.0 microinches threads
Produc	t Name:
Navy sp	pecial project
Specia	Features:
Tapped	hole in head 0.138-32 unjc-3b threads. Distance from top of head to injection port 0.510 nom. Inch. Injection port 0
	om. In. Wide
Materia	d:
Titaniur	n alloy uns r56400
	I Specification:
	28 assn standard single material response or ams 4967 assn standard single material response
	e Treatment:
Phosph	
-	Series Designator:
Unjf	
Shelf L	ife:
N/a	
	Measure:

## NSN 5305-01-337-4859

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

