NSN 5305-01-337-4865

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-4865

Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 1.751 inches and 1.781 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.708 inches and 0.765 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.178 inches and 1.198 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads **Special Features:** Red dye or paint on thread end before lubrication Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Bac 5861, cage81205 mfr ref single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5305-01-337-4865

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0