NSN 5305-01-337-4879

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-4879

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.578 inches
Fastener Length:
Between 1.501 inches and 1.591 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.691 inches and 0.765 inches
Grip Diameter:
Between 0.3740 inches and 0.3745 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
24
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-337-4879

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

