## NSN 5305-01-337-4880

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-4880

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.578 inches  |
| Fastener Length:  |
| Between 1.875 inches and 1.905 inches   |
| Head Style:   |
| Flat countersunk  |
| Head Diameter:  |
| Between 0.691 inches and 0.765 inches   |
| Grip Diameter:  |
| Between 0.3740 inches and 0.3745 inches                                       |
| Internal Drive Style:   |
| High-torque   |
| Thread Diameter:  |
| 0.375 inches  |
| Grip Length:  |
| Between 1.302 inches and 1.322 inches   |
| Thready Qty Per Inch (tpi):   |
| 24  |
| Countersink Angle:  |
| Between 99.0 degrees and 101.0 degrees  |
| Surface Finish:   |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches |
| Material:   |
| Nickel alloy 718  |
| Material Specification:   |
| Ams 5662 assn standard single material response                               |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response                       |
| Thread Series Designator:   |
| Unjf  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |
| Demilitarization:   |
| No  |
|   |

threads

## NSN 5305-01-337-4880

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

