## NSN 5305-01-337-4891

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-4891

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.469 inches	
Fastener Length:	
Between 1.204 inch	es and 1.234 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.456 inch	es and 0.508 inches
Grip Diameter:	
Between 0.2490 inc	hes and 0.2495 inches
Internal Drive Style	
High-torque	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 0.740 inch	es and 0.760 inches
Thready Qty Per In	ch (tpi):
28	
Countersink Angle	:
Between 99.0 degre	es and 101.0 degrees
Surface Finish:	
32.0 microinches be	aring surface of head32.0 microinches grip32.0 microinches threads
Product Name:	
Navy special project	
Special Features:	
Tapped hole in head	10.138-32 unjc-3b threads. Distance from top of head to injection port 0.530 nom. Inch. Injection port 0.120 nom. In. L
0.060 nom. In. Wide	
Material:	
Titanium alloy uns r	56400
Material Specificat	ion:
Ams 4928 assn star	dard single material response or ams 4967 assn standard single material response
Surface Treatment	
Phosphate	
Thread Series Desi	gnator:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5305-01-337-4891

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

