NSN 5305-01-337-5438

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5438 **Thread Class:** 2a **Thread Direction:** Right-hand Fastener Length: Between 1.190 inches and 1.250 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.174 inches and 0.184 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Primary Washer Outside Diameter:** Between 0.495 inches and 0.505 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.041 inches and 0.051 inches **Special Features:** Semi-gloss paint, cloud gray per federal 595 Color: Gray fastener Material: Plastic polyamide primary washersteel comp 301 fastener or steel comp 302 fastener or steel comp 302 fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fast fastener or steel comp 316 fastener or steel comp 316 fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener **Surface Treatment:** Paint fastener **Thread Series Designator:**

Domilitarization.

Unit Of Measure:

Unf

N/a

Shelf Life:

NSN 5305-01-337-5438

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0