NSN 5305-01-337-5446

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5446

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.363 inches |
| Fastener Length: |
| Between 0.909 inches and 0.956 inches |
| Head Style: |
| Flat countersunk undercut |
| Head Diameter: |
| Between 0.350 inches and 0.381 inches |
| Head Height: |
| Between 0.044 inches and 0.046 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.552 inches and 0.572 inches |
| Features Provided: |
| O ring |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Material: |
| Rubber butadiene-acrylonitrile class nbr ringnickel alloy 718 fastener |
| Material Specification: |
| Ams 5662 assn standard single material response fastener |
| Surface Treatment: |
| Passivate fastener |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-337-5446

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

