## NSN 5305-01-337-5447

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5447

Thread Class:	
3a	
Thread Direction	:
Right-hand	
Thread Length:	
0.469 inches	
Fastener Length	
Between 0.954 in	ches and 0.984 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.456 in	ches and 0.508 inches
Grip Diameter:	
Between 0.2490 i	nches and 0.2495 inches
Internal Drive St	/le:
High-torque	
Thread Diameter	
0.250 inches	
Grip Length:	
Between 0.490 in	ches and 0.510 inches
Thready Qty Per	Inch (tpi):
28	
Countersink Ang	le:
Between 99.0 deg	rees and 101.0 degrees
Surface Finish:	
32.0 microinches	pearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:	
Navy special proje	ect
Special Features	:
Tapped hole in he	ad 0.138-32 unjc-3b threads. Distance from top of head to injection port 0.260 nom. Inch. Injection port 0.120 nom. In. Lo
0.060 nom. In. Wi	de
Material:	
Titanium alloy une	r56400
Material Specific	ation:
Ams 4928 assn si	andard single material response or ams 4967 assn standard single material response
Surface Treatme	nt:
Phosphate	
Thread Series De	esignator:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure	

## NSN 5305-01-337-5447

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

