NSN 5305-01-337-5461

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5461 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 1.016 inches and 1.046 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.456 inches and 0.508 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Product Name:

Navy special project

Special Features:

Tapped hole in head o.138-32 unjc-3b threads. Distance from top of head to injection port 0.340 nom. Inch. Injection port 0.120 nom. In. Lg; 0.060 nom. In. Wide

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Phosphate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-337-5461

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0