NSN 5305-01-337-5462

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5462

| View Online at https://aerobasegroup.com/nsn/5305-01-337-5462 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.469 inches |
| Fastener Length: |
| Between 1.016 inches and 1.046 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.456 inches and 0.508 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.552 inches and 0.572 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Product Name: |
| Navy special project |
| Special Features: |
| Tapped hole in head 0.138-32 unjc-3b threads. Distance from top of head to injection port 0.280 nom. Inch. Injection port 0.120 nom. In. Lg; |
| 0.060 nom. In. Wide |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment: |
| Phosphate |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-337-5462

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0