NSN 5305-01-337-5465

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5465

| Thread Class: | |
|------------------------|---|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.469 inches | |
| Fastener Length: | |
| Between 0.954 inches | and 0.984 inches |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 0.456 inches | and 0.508 inches |
| Grip Diameter: | |
| Between 0.2490 inche | is and 0.2495 inches |
| Internal Drive Style: | |
| High-torque | |
| Thread Diameter: | |
| 0.250 inches | |
| Grip Length: | |
| Between 0.490 inches | and 0.510 inches |
| Thready Qty Per Inc | n (tpi): |
| 28 | |
| Countersink Angle: | |
| Between 99.0 degree | and 101.0 degrees |
| Surface Finish: | |
| 32.0 microinches bea | ing surface of head32.0 microinches grip32.0 microinches threads |
| Product Name: | |
| Navy special project | |
| Special Features: | |
| | 0.138-32 unjc-3b threads. Distance from top of head to injection port 0.280 nom. Inch. Injection port 0.120 nom. In. Lo |
| 0.060 nom. In. Wide | |
| Material: | |
| Titanium alloy uns r56 | 400 |
| Material Specificatio | |
| | ard single material response or ams 4967 assn standard single material response |
| Surface Treatment: | |
| Phosphate | |
| Thread Series Desig | nator: |
| Unjf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |

NSN 5305-01-337-5465

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

