NSN 5305-01-337-5963

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5963 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.363 inches **Fastener Length:** Between 0.972 inches and 1.019 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.350 inches and 0.381 inches **Head Height:** Between 0.044 inches and 0.046 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.615 inches and 0.635 inches **Features Provided:** O ring Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Rubber butadiene-acrylonitrile class nbr ringnickel alloy 718 fastener **Material Specification:** Ams 5662 assn standard single material response fastener **Surface Treatment:** Passivate fastener **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-337-5963

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0