## NSN 5305-01-337-5976

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5976

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.768 inches
Fastener Length:
Between 1.172 inches and 1.219 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.966 inches and 1.014 inches
Head Height: Between 0.157 inches and 0.160 inches
Grip Diameter: Between 0.4990 inches and 0.4995 inches
Internal Drive Style:
High-torque Thread Diameter:
0.500 inches
Grip Length: Between 1.178 inches and 1.198 inches
Features Provided:
O ring
-
Thready Qty Per Inch (tpi):
20 Countersink Angles
Countersink Angle:
Between 99.0 degrees and 101.0 degrees Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material:
Rubber butadiene-acrylonitrile class nbr ringnickel alloy 718 fastener
Material Specification:
Ams 5662 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Thread Series Designator:
Unjf Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-337-5976

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

