## NSN 5305-01-337-5987

Close Tolerance Screw - Page 1 of 2



0.880 nom. Inch. Injection port 0.120 nom. In. Lg;

View Online at https://aerobasegroup.com/nsn/5305-01-337-5987

Thread Cla	SS:
3a	
Thread Dire	ection:
Right-hand	
Thread Ler	ngth:
0.641 inche	S
Fastener L	ength:
Between 1.	814 inches and 1.844 inches
Head Style	:
Flat counter	rsunk
Head Diam	eter:
Between 0.	692 inches and 0.763 inches
Grip Diame	eter:
Between 0.	3740 inches and 0.3745 inches
Internal Dr	ive Style:
High-torque	
Thread Dia	meter:
0.375 inche	S
Grip Lengt	h:
Between 1.	178 inches and 1.198 inches
Thready Q	y Per Inch (tpi):
24	
Countersin	k Angle:
Between 99	0.0 degrees and 101.0 degrees
Surface Fir	nish:
32.0 microii	nches bearing surface of head32.0 microinches grip32.0 microinches threads
Special Fea	atures:
Tapped hol	e in head 0.138-32 unjc-3b threads. Distance from top of head to injection port 0.880 nom. Inc
0.060 nom.	In. Wide
Material:	
Titanium all	oy uns r56400
Material Sp	pecification:
Ams 4928 a	assn standard single material response or ams 4967 assn standard single material response
Surface Tr	eatment:
Phosphate	
Thread Ser	ies Designator:
Unjf	
Shelf Life:	
N/a	
Unit Of Me	asure:
 Demilitariz	ation
No	

## NSN 5305-01-337-5987

Close Tolerance Screw - Page 2 of 2

**Fiig:** A003b0

